

# RUBAN LED

# ALFA EVO ALFA EVO COLOR



IRC  
≥90

IP 20 / IP 65

CLASSE  
III

GARANTIE  
5 ANS

50 000h

CE

RoHS

12V

\*En fonction du matériel utilisé


IP20

IP65

## CARACTÉRISTIQUES TECHNIQUES | ALFA EVO COLOR




Puissance	Réf.	IP	Température de couleur
14.4W	806040 <span style="color:red">■</span>	-	RGB
	<span style="color:red">■</span> 020	IP20	R - 147 lm/m G - 517 lm/m B - 104 lm/m RGB = 753 lm/m
	<span style="color:red">■</span> 420	IP65	

 IP20 / IP65 = 8mm  
Coupe 14.4W = 50mm  
60 Led/m  
Longueur maximum conseillée = 5m

► Coupe 14.4W = Tous les 5cm  
0 - 5 - 10 - 15 - 20 - 25 - 30 - 35 - 40 - 45 - 50 - 55 - 60 - 65 - 70 - 75 - 80 - 85 - 90 - 95 - 100


## CARACTÉRISTIQUES TECHNIQUES | ALFA EVO

Puissance	Réf.	IP	Température de couleur
6W	812080 <span style="color:red">■</span> <span style="color:blue">■</span>	-	-
	<span style="color:red">■</span> 0	IP20	<span style="color:blue">■</span> 03 3000K <span style="color:orange">■</span> 570 lm/m
	<span style="color:red">■</span> 4	IP65	<span style="color:blue">■</span> 04 4000K <span style="color:yellow">■</span> 660 lm/m

 IP20 / IP65 = 8mm  
Coupe 6W = 25mm  
120 Led/m  
Longueur maximum conseillée = 5m

► Coupe 6W = Tous les 2.5cm  
0 - 2.5 - 5 - 7.5 - 10 - 12.5 - 15 - 17.5 - 20 - 22.5 - 25 - 27.5 - 30 - 32.5 - 35 - 37.5 - 40 - 42.5 - 45 - 47.5 - 50 - 52.5 - 55 - 57.5 - 60 - 62.5 - 65 - 67.5 - 70 - 72.5 - 75 - 77.5 - 80 - 82.5 - 85 - 87.5 - 90 - 92.5 - 95 - 97.5 - 100

Puissance	Réf.	IP	Température de couleur
12W	812090 <span style="color:red">■</span> <span style="color:blue">■</span>	-	-
	<span style="color:red">■</span> 0	IP20	<span style="color:blue">■</span> 03 3000K <span style="color:orange">■</span> 1040 lm/m
	<span style="color:red">■</span> 4	IP65	<span style="color:blue">■</span> 04 4000K <span style="color:yellow">■</span> 1210 lm/m

 IP20 / IP65 = 8mm  
Coupe 12W = 25mm  
120 Led/m  
Longueur maximum conseillée = 5m

► Coupe 12W = Tous les 2.5cm  
0 - 2.5 - 5 - 7.5 - 10 - 12.5 - 15 - 17.5 - 20 - 22.5 - 25 - 27.5 - 30 - 32.5 - 35 - 37.5 - 40 - 42.5 - 45 - 47.5 - 50 - 52.5 - 55 - 57.5 - 60 - 62.5 - 65 - 67.5 - 70 - 72.5 - 75 - 77.5 - 80 - 82.5 - 85 - 87.5 - 90 - 92.5 - 95 - 97.5 - 100

